

	V350-35-R2	V350-35-R34	V350-35-RA22	V350-35-T2	V350-35-T38	V350-35-TA24
	10 Digital Inputs 2 Analog/Digital Inputs 6 Relay Outputs	20 Digital Inputs 2 Analog/Digital Inputs 12 Relay Outputs	8 Digital Inputs 2 Analog/Digital Inputs 2 TC/PT/Digital Inputs ¹ 8 Relay Outputs 2 Analog Outputs	10 Digital Inputs 2 Analog/Digital Inputs 12 Transistor Outputs	20 Digital Inputs 2 Analog/Digital Inputs 16 Transistor Outputs	8 Digital Inputs 2 Analog/Digital Inputs 2 TC/PT/Digital Inputs ¹ 10 Transistor Outputs 2 Analog Outputs
I/O						
Digital Inputs ¹ (maximum)	12 pnp/npn (source/sink) 24VDC	22 pnp/npn (source/sink) 24VDC	12 pnp/npn (source/sink) 24VDC	12 pnp/npn (source/sink) 24VDC	22 pnp/npn (source/sink) 24VDC	12 pnp/npn (source/sink) 24VDC
High-speed Counters/Shaft-Encoder/Frequency Measurer ²	Three, 10 kHz 32 bit resolution	Three, 10 kHz 32 bit resolution	One, 10 kHz 32 bit resolution	Three, 10 kHz 32 bit resolution	Two, 10 kHz 32 bit resolution	One, 10 kHz 32 bit resolution
Analog Inputs ¹	Two 10 bit inputs: 0-10V, 0-20mA, 4-20mA	Two 10 bit inputs: 0-10V, 0-20mA, 4-20mA	Two 14 bit inputs: 0-10V, 0-20mA, 4-20mA and	Two 10 bit inputs: 0-10V, 0-20mA, 4-20mA	Two 10 bit inputs: 0-10V, 0-20mA, 4-20mA	Two 14 bit inputs: 0-10V, 0-20mA, 4-20mA and
Temperature Measurement ¹	None	None	2 PT100 or Thermocouple inputs	None	None	2 PT100 or Thermocouple inputs
Digital Outputs	6 relay outputs	12 relay outputs	8 relay outputs	12 pnp (source)	16 pnp (source)	10 pnp (source)
High-speed Outputs/PWM ²	None	None	None	Seven, 2 kHz	Seven, 2 kHz	Five, 2 kHz
Analog Outputs	None	None	Two 12 bit outputs: 0-10V, 4-20mA	None	None	Two 12 bit outputs: 0-10V, 4-20mA
I/O Expansion	Up to 128 I/Os may be added via I/O expansion port (number of I/Os may vary according to expansion module)					
Operator Panel						
Display	320x240 pixels (QVGA), 3.5" active area , Graphic TFT LCD					
Touchscreen	Resistive, analog					
Colors	256					
HMI Displays	1024 displays, 250 images per application					
Keyboard	5 programmable keys. Labeling options - function keys, arrows or customized					
Program						
Application Memory	Application Logic: 1MB • Images: 3MB • Fonts: 512K					
Scan Time	15µsec per 1K of typical application					
Operand Capacity	8192 coils, 4096 registers, 512 long integers (32 bit), 256 double words (32 bit unsigned), 64 floats, 384 timers (32 bit), 32 counters Additional non-retainable operands: 1024 X-bits, 512 X-integers, 255 X-long integers, 64 X-double words					
Data Tables	120K dynamic data (recipe parameters, datalogs, etc'), 192K fixed data (read-only data, ingredient names, etc)					
Enhanced Programming Features	Trends: graph any value • Alarms: built-in screens • String Library: Instantly switch HMI language					
Communication						
RS232/RS485	1 built-in RS232/RS485 port (selectable)					
Optional port ³	Ethernet (V100-17-ET2)	or	RS232/RS485 (V100-17-RS4)	or	RS232/RS485 (isolated) (V100-17-RS4X)	
CANbus port ³ (optional)	1 isolated port (V100-17-CAN). Supports CANopen, UniCAN and CAN Layer 2					
MODBUS	Supports MODBUS protocol, Master/Slave					
GPRS	Programming, data acquisition and SMS, via wireless data transmission					
GSM	SMS messages to/from any quantity of phone numbers					
General						
PID	Up to 24 independent PID loops, including internal auto-tune, ramp-soak programmer and bumpless transfer					
Power supply	24VDC					
Battery back-up	7 years typical at 25°C					
Dimensions	External: 109.1 x 114 x 68 mm (4.29" x 4.49" x 2.67") ; Cut-out: 92 x 92 mm (3.622" x 3.622")					
Environment	IP65/NEMA4X (for panel, when mounted)					